



Anemomaster

Model 6113/6114

High velocity, multi-function hot-wire Anemometer

Features

- Simultaneous measurements of air velocity, temperature, and differential pressure.
- Large, easy-to-read LCD display
- Model 6113 includes built-in printer
- Complete with probe, 79 in (200cm) cable, extension rod, shoulder-strap, 6 pcs C cell batteries, and NIST Certificate



Specifications

Model	6113	6114
Air Velocity Ranges	2 to 9840 fpm (0.01 to 50.0 m/s)	
Accuracy	+/- (3% of reading + 0.1 m/s)	
Temperature Ranges	32 to 212 °F (0 to 100 °C)	
Accuracy	+/- 2.0 °F (1.0 °C)	
Differential Pressure Ranges	+/- 5.00 kPa *Option	
Accuracy	+/- (3% of reading + 0.01) kPa	
Interface	RS232C	
Datalogging	100 measurements	
Analog Output (Option)	0 to 1 V *Option	
Built-in Printer	Yes	No
Power Supply	6 x C cell Batteries	
Dimensions	W7.9 x H5.9" x D3.9"	
Weight	2.2 lbs (1 kg)	



Accessories

- 6113-01: Spare Probe
- 6113-03: Extension Rod
- 6113-07: Pressure Sensor
- S600-00: Data Processing Software
- 6000-02: Communication Cable to PC
- TP-202L: Rolled Printer Paper (10 rolls)
- 6113-02: AC Adapter
- 6113-04: Shoulder Strap
- 6113-08: Analog Output
- 6000-02: Communication Cable to PC



P2M (THAILAND) CO. LTD
 75/8 Moo. 11, T.Klong Nueng, A. Klong Luang,
 Pathumthani 12120. Thailand
 Tel. (66) 0 2520 3976-9 Fax. (66) 0 2520 3998
 Email : sales@p2mgroup.com.
 Website : www.p2mgroup.com

